

BRADY B-659 GLOSSY BACKLIT FILM

TDS No. B-659
Effective Date: 09/15/1998

Description:

General use inkjet printable backlit film

Details:

Box ID:

CPP FILM M

Use:

Indoor backlit graphic displays for trade shows, malls, airports

Characteristics:

High quality images
Fast dry times
High whiteness and high opacity
Useful for both backlight and reflected light use

To be used with:

ColorPix™ 3600 System
ColorPix™ Pro 36 System
ColorPix™ Pro 54 System

Media Type:

Coated polyester film

Typical Weight:

86 lbs/3000 ft² (140g/m²)

Total Thickness:

0.0049" (0.125 mm)

Material Length/Packaging Unit/Box:

24" x 35' x 2 roll (610 mm x 30 meters)
36" x 45' x 1 roll (915 mm x 45 meters)

Image Durability:

Life of the graphic is dependent upon finishing and environment

Shelf Life:

18 months in the conditions of 73°F (23°C) and 50 to 60% RH

Transportation Temperature:

50°F to 86°F (10°C to 30°C)

Recommended Printing Temperature:

59°F to 91°F (15°C to 33°C)

Remarks:

Droplets of water will make spots on the surface of printout and reduce quality. If the printout is stored in high temperature and humidity, the printout tends to become slightly red in color.

Trademarks:

ColorPix™ is a trademark of Brady Worldwide, Inc.
All U.S. Conventional Units are mathematically derived from the S.I. (metric)

Units

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide, Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289