

Order reference	AW124					
Article number	813791					
Date 4-	1-11	Replaces	6-28-06	No. Pages	1	

Product Description:

Style	SOC	
Item Size (each)	7.6 cm d x 366 cm long	
Color	Gray with black logo printing	
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %	
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)	
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)	
Technology	Meltblown + Spunbond + Sealed or Enclosed ends	
Absorbency	Hydrophilic + Oleophilic	
Intended Application	Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil	
	Base, or Solvent Base Liquids	

Packaging Description:

I dendging Deseription			
Package configuration	Case	Pkg. Weight	5.3kg (4.3kg)
Items per Package	4 SOCS/Case	Pkg. Dimensions (approx.)	56.5cm x 32cm x
			37.5cm
Container type	Carton		

Physical Properties;

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	kg	1.08	0.27
Absorbency** (med.	SPCTM-012B	gL/gS	9.0	8-min.
oil)				
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
_	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com