

Order reference	AW430
Article number	813788

Date	4-11-11	Replaces	6-28-06	No. Pages	1

Product Description:

Style	SOC
Item Size (each)	7.6 cm dia x 122 cm long
Color	Gray with black logo printing
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)
Technology	Meltblown + Spunbond + Sealed or Enclosed Ends
Absorbency	Hydrophilic + Oleophilic

Intended Application	Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil
	Base, or Solvent Base Liquids

Absolution Capacity 113 1 Del Dale Asatulated, inculuin viscosity- 787	Absorbency Capacity	113 l per bale (saturated; medium viscosity- 9x)	
--	---------------------	--	--

Packaging Description:

Package configuration	Case	Pkg. Weight	12.0kg (10.8kg)
Items per Package	30 SOCS/Case	Pkg. Dimensions (approx.)	65 cm x 44 cm x
			54 cm
Container type	Carton		

Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
SOC Weight	Gravimetric	kg	0.36	0.09
Absorbency** (med.	SPCTM-012B	gL/gS	9.0	8-min.
oil)				
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.