

BRADY B-992 GLOSSY SELF-LAMINATING FLUID LINE TUBE AND PIPE MARKER TAPE

TDS No. B-992
 Effective Date: 10/27/2011

Description:

Brady Glossy Self-laminating Tube and Pipe Marker is a glossy transparent polyester tape with a permanent acrylic adhesive, topside printed with an opaque thermal transfer printable portion and a clear end for self-laminating.

Brady Series R6000 thermal transfer ribbon is recommended for use with the Brady Glossy Self-Laminating Tube and Pipe Marker Tape.

Details:

Adhesion tests performed on QQ-A-250/5 aluminum panels. Adhesion samples dwelled at room temperature for 72 hours prior to exposing to test condition. Adhesions tested within 15 minutes after removal of the panels from the test fluids.

Property	Test Method	Precondition	Average Result
Total Thickness	ASTM D 3652	NA	0.002 inch
Tensile Strength	ASTM D 3759	NA	31 lbs/in.
Elongation	ASTM D 3759	NA	90%
Adhesion	ASTM D 3330, Method A	Initial Adhesion 72 hour dwell	56 oz/in.
		Accelerated Weathering (ASTM-G-155, cycle 1), 96 hours	70 oz/in.
		Adhesive Stability (ASTM-G-155, cycle 1 no water), 20 hours	27 oz/in.
		Water Immersion, 24 hour	40 oz/in.
		JP-5 Immersion (MIL-DTL-5624), 72 hour	41 oz/in.
		JP-8+100 Immersion (MIL-DTL-83133), 72 hour	36 oz/in.
		Lubricating Oil @ 200F Immersion (MIL-L-7808), 24 hour	50 oz/in.
		Hydraulic Fluid Immersion (MIL-PRF-5606), 72 hour	41 oz/in.
		Hydraulic Fluid Immersion (MIL-H-83282), 72 hour	35 oz/in.
Heat Resistance	MIL-T-9906C	100 hours at 325F (163C)	Adhesive discolors but print remains legible
Water Vapor Transmission	ASTM D3833	NA	1.20g H ₂ O/100 in ² /24 hrs

Product testing, customer feedback, and history of similar products, support a customer performance expectation of at least **two years from the date of receipt** for this product as long as this product is stored in its original packaging in an environment *below 80 degrees F (27°C) and 60% RH*. We are confident that our product will perform well beyond this time frame. However, it remains the responsibility of the user to assess the risk of using such product. We encourage customers to develop functional testing protocols that will qualify a product's fitness for use, in their actual applications.

Trademarks:

ASTM: American Society for Testing and Materials (U.S.A.)

Note: All values shown are averages and should not be used for specification purposes.

Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties, express or implied, and assumes no liability in connection with the use of this information.

WARRANTY

Brady products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses. Brady warrants to the buyers that its products are free from defects in material and workmanship, but limits its obligation under this warranty to replacement of the product shown to Brady's satisfaction to have been defective at the time Brady sold it. This warranty does not extend to any persons obtaining the product from the buyers. This warranty is in lieu of any other warranty, express or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose, and of any other obligations or liability on Brady's part. Under no circumstances will Brady be liable for any loss, damage, expense, or consequential damages of any kind arising in connection with the use, or inability to use, Brady's products.

Copyright 2016 Brady Worldwide, Inc. | All Rights Reserved
Material may not be reproduced or distributed in any form without written permission.

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289