

TECHNICAL DATA SHEET

Order reference	GP200-M
Article number	813813

Date	4-11-11	Replaces	03-27-07	No. Pages	1

Product Description:

I Toutet Description.	
Style	Pads; perforated on centerline for dividing in half for smaller applications
Item Size (each)	41 cm x 51 cm perf at 25.5 cm
Color	Gray
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1
Structure	A nonwoven mat of randomly oriented Micro-fibers [2-10 micron diameters]
Technology	Meltblown
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Bonded (staggered pattern) + Mechanical entanglement

Intended Application	Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids

Absorbency Capacity	166 l per box (saturated; medium viscosity-18x)

Packaging Description:

Package configuration	Case	Pkg. Weight	9.6 kg (7.9 kg)
Items per Package	200-Pads/Case	Pkg. Dimensions	53cm x 43cm x 55 cm H
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	190	19
Caliper	SPCTM-020	mm	4	0.4
Absorbency ** (med.	SPCTM-004B	gL/gS	18	1.8
Oil)				
Tensile strength	SPCTM-007	daN	5,5	0.5
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	