

| Order reference | HAZ124 |
|-----------------|--------|
| Article number | 813852 |

| Date | 4-11-11 | Replaces | 6-29-06 | No. Pages | 1 |
|------|---------|----------|---------|-----------|---|
| | | | | | |

Product Description:

| I Todact Description: | |
|-----------------------|---|
| Style | SOC |
| Item Size (each) | 7.6 cm d x 366 cm long |
| Color | Green with green logo printing |
| Composition | Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 % |
| Structure | Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters) |
| | Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber) |
| Technology | Meltblown + Spunbond + Sealed or Enclosed Ends |
| Absorbency | Hydrophilic + Oleophilic |

| Intended Application | Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil |
|-----------------------------|---|
| | Base, or Solvent Base Liquids |

| | 1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 |
|----------------------|---|
| A hearhancy Canacity | 45 l per case (saturated; medium viscosity- 9x) |
| Absorbency Capacity | 1 45 i per case (saturated, inediam viscosity)x) |

Packaging Description:

| Package configuration | Case | Pkg. Weight | 5.3 kg (4.4kg) |
|-----------------------|-------------|---------------------------|------------------------|
| Items per Package | 4 SOCS/Case | Pkg. Dimensions (approx.) | 56.5cm x 32cm x 37.5cm |
| Container type | Carton | | |

Physical Properties;

| <u>Parameter</u> | SPC Test Method | <u>Units</u> | Nominal Nominal | (+/-)Tolerance |
|-------------------------|-----------------|--------------|-----------------|----------------|
| SOC Weight | Gravimetric | kg | 1.08 | 0.27 |
| Absorbency** (med. oil) | SPCTM-012B | gL/gS | 9 | 8-min. |
| Color | Visual | | Green | per standard |

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

| Attributes | Product will be free of foreign material contamination, rips, holes, and tears. |
|---------------|---|
| Labeling | Each package to be clearly labeled with Company Name, Address, Item No., |
| | Date, and/or Package Code (Bar Code). |
| Certification | Make no changes in basic process or composition without notifying customer. |
| | Claims for non-conformance of goods must be made within 60-days of delivery. |