

TECHNICAL DATA SHEET

Catalog #: 149284, 149285

www.bradyid.com

°C

Fuse Lockout - GE NEC

Design

- Designed to secure GE NEC fuse blocks
- Easy, quick and assured safety lock out
- Non-conductive, rugged ABS material
- Add safety padlock to complete the lockout .
- Optional lockout by use of nylon zip tie also possible



Chemical


°C



Chemical

	Acetone	25	Petroleum	25
Material	Acetone	60	Turpentine oil	25
Made of ABS	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
 Color: Red (PMS 1805C) UL Rating: UL94 - HB Rating 	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
Temperature Range	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
 -20° to 120°C (0° to 250°F) 	Fuel, engine: M15 mixture (15%) methanol)	70	Water (including seawater)	25
Chemical Resistance	Methanol	25	etc.	ХХ
If desired, list all approved chemicals based on the manufacturer's specified chemical resistance chart for component materials. See table at right with sample chemicals and temperatures: Dimensions List dimensions with appropriate labels:	ŧ			L

" A "	-	0.70" [17.8 mm]
"B"	-	2.56" [65.0 mm]
"C"	-	2.29" [58.2 mm]
"D"	-	0.44" [11.2 mm]



Warranty

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by Brady customers for designs and specifications, or be relied on as meeting specified performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact Brady for further information.

Product compliance information is based upon information provided by suppliers of the raw materials used by Brady to manufacture this product or based on results of testing using recognized analytical methods performed by a third party, independent laboratory. As such, Brady makes no independent representations or warranties expressed or implied, and assumes no liability in connection with the use of this information.

MSDS Information

Brady North America | 6555 W. Good Hope Rd | Milwaukee, WI 53223 | USA | Tel: 414-358-6600 | Fax: 800-292-2289

1. HAZARDS IDENTIFICATION

This product is NOT DANGEROUS and contains no hazardous ingredients.

2. FIRST AID MEASURES/HEALTH INFORMATION /PROTECTION

Eye Contact:	Not applicable, product is inert	
Ingestion:	Not applicable, first aid is not normally required.	
Inhalation:	Not applicable	
Skin Contact:	Not applicable, product is inert, except if product is melted use gloves. For hot melted product, immerse in or flush affected area with water to dissipate heat, and then obtain medical attention.	
Exposure Limits:	None	
Threshold Limits	None	
Personal Protection:	None (ambient conditions)	
NPCA-HMIS Rating:	Health: 0; Flammability: 1; Reactivity: 0	
NFPA-704 Rating:	Health: 0; Flammability: 1; Reactivity: 0	

3. FIRE-FIGHTING MEASURES

Be cautious of hot melted Nylon	Use water spray to cool fire, exposed surfaces, and to protect personnel
Isolate product from fire	 Respiratory and eye protection is required for fire fighting personnel
Extinguish fire with water spray	 Decomposition products under fire conditions: Oxygen-lean conditions may cause monoxide and irritating smoke

4. ACCIDENTAL RELEASE MEASURES

Land	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.
Water	Recover material and place in suitable container for reuse or for disposal in conformance with local regulations.

5. HANDLING AND STORAGE

5.1 Handling	5.2 Storage
No precautions noted - see local regulation if needed	Storage Pressure: Atmospheric
	Storage Temperature: Ambient, no direct sunlight

6. EXPOSURE CONTROLS/PERSONAL PROTECTION

6.1 Exposure Limit Values	6.2 Exposure Controls	
None	6.2.1 Occupational Exposure Controls	
	6.2.1.1 Respiratory Protection: Not applicable	
	6.2.1.2 Hand Protection: Not applicable	
	6.2.1.3 Eye Protection: Not applicable	
	6.2.1.4 Skin Protection: Not applicable	
	6.2.2 Environmental Exposure Controls: No data available	

7. PHYSICAL AND CHEMICAL PROPERTIES

General Information	
Other Information	

8. STABILITY AND REACTIVITY

8.1 Conditions to Avoid

Higher Temperatures and direct sunlight (chemical resistance is excellent)		
Highly stable, but temperatures over 480 F may cause degradation		
8.2 Materials to Avoid		
No data available		
8.3 Hazardous Decomposition Products		
Under fire and oxygen-lean conditions may cause monoxide and irritating smoke		

9. ECOLOGICAL INFORMATION

9.1 Ecotoxicity	No data available
9.2 Mobility	No data available
9.3 Persistence and Degradability	No data available
9.4 Bioaccumulative Potential	No data available
9.5 Other Adverse Effects	No data available

10. DISPOSAL CONSIDERATIONS

None of the materials in this product are Recyclable, dispose of all materials in accordance with an applicable federal, state, and local law.

11. TRANSPORT INFORMATION

No data available

12. REGULATORY INFORMATION

This product has been tested and validated to the Regulatory Requirements listed below:			
•	OSHA 29 CFR 1910.147 ©(4)(ii)(A)(1)/(c)(5)(ii)(C)(1)	•	ANSI Standard Z244

13. OTHER INFORMATION

No data available