

TECHNICAL DATA SHEET

Order reference MRO100-E
Article number 813809

Date	4-11-11		Replaces	03-31-08		No. Pages	1
------	---------	--	----------	----------	--	-----------	---

Product Description:

41 cm x 51 cm	
Gray	
Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %	
96% natural white meltblown nonwoven fibers(<10 microns)	
4% white spunbond nonwoven coverstock(<15-30 microns)	
Meltblown + spunbond	
Universal (Hydrophilic + Oleophilic)	
Bonded (staggered pattern) + Mechanical entanglement	
Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids	

Packaging Description:

Package configuration	1-Case	Pkg. Weight	8.6 kg (7.6 kg)
Items per Package	100-Pads/Case	Pkg. Dimensions	53 cm x 43 cm x 43 cm H
Container type	Carton		

Physical Properties:

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	365	36
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	12.5	1.2
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com