

TECHNICAL DATA SHEET

Order reference MRO15-P-E								
Article number		8138	18					
Date	4-11-11		Replaces	03-	31-08	No. Pages	1	

Product Description:

Style	Blanket Roll; high strength perforation every 46 cm for single or multiple/variable length pads
Item Size (each)	38 cm wide by 46 m long (100 Pads)
Color	Gray
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %
Structure	96% natural white meltblown nonwoven fibers(<10 microns) 4% white spunbond nonwoven coverstock(<15-30 microns)
Technology	Meltblown + spunbond
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Bonded (staggered pattern) + Mechanical entanglement

Absorbency Capacity	94 1 per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	Case	Pkg. Weight	7.5 kg (6.4 kg)
Items per Package	1 Roll / Case	Pkg. Dimensions	46cm x 46cm x
	100 pads		40cm H
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	365	36
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency ** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	12.5	1.2
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.				
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,				
	Date, and/or Package Code (Bar Code).				
Certification	Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.				