

TECHNICAL DATA SHEET

Order reference	MRO150-DND-E
Article number	813811

Date	4-11-11	Replaces	03-31-08	No. Pages	1

Product Description:

<u>I Toudet Description.</u>				
Style	Pads; perforated on centerline for dividing in half for smaller applications			
	Packaging; "Dispense & Dispose" carton for easy pad access.			
	Carton also contains two disposal bags for containment of used pads.			
Item Size (each)	41 cm x 51cm			
Color	Gray			
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %			
Structure	96% natural white meltblown nonwoven fibers(<10 microns)			
	4% white spunbond nonwoven coverstock(<15-30 microns)			
Technology	Meltblown + spunbond			
Absorbency	Universal (Hydrophilic + Oleophilic)			
Bonding	Bonded (staggered pattern) + Mechanical entanglement			
Intended Application	Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids			

Absorbency Capacity	168 l per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	1-Case	Pkg. Weight	14.0 kg (11.6 kg)
Items per Package	150-Pads/Case + 2	Pkg. Dimensions	54.5 cm x 45 cm
	disposal bags		x 64 cm H
Container type	Dispenser Carton		

Physical Properties;

i il joieur i i o per debi,				
Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	365	36
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	12.5	1.2
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com