

Order ref	erence	MRO3	80-Е				
Article number		813822	2				
	4 11 1				N. D.	1	
Date	4-11-1	1	Replaces	03-31-08	No. Pages	1	

Style	Blanket Roll
Item Size (each)	76 cm wide by 46 m long
Color	Gray
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %
Structure	96% natural white meltblown nonwoven fibers(<10 microns)
	4% white spunbond nonwoven coverstock(<15-30 microns)
Technology	Meltblown + spunbond
Absorbency	Universal (Hydrophilic + Oleophilic)
Bonding	Bonded (staggered pattern) + Mechanical entanglement
Intended Application	Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids

Absorbency Capacity	187 1 Per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	Case		Pkg. Weight	14.6 kg (12.9 kg)
Items per Package	1 Bale / Case	-	Pkg. Dimensions	45.5cm x 45.5cm x 78.5cm H
Container type	Carton			

Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	365	36
Caliper	SPCTM-020	mm	5.3	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	12.5	1.2
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.			
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,			
	Date, and/or Package Code (Bar Code).			
Certification Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.			
Brady Europe Industriepark C3 Lindestraat 20 B9240 Zele Belgium				

e | Industriepark C3 Lindestraat 20 | B9240 Zel Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com