

## **TECHNICAL DATA SHEET**

Order reference MRO330-DP-E			]					
Article number		81382	5					
Date	4-11	-11		Replaces	03-31-08	No. P	ages	1

## **Product Description:**

Style	Economical Blanket Roll; perforated down the middle for the 38cm wide				
-	dimension, & cross-wise for the 38cm long dimension.				
Item Size (each) 76cm wide by 46m long (240 pads per roll)					
Color	Gray				
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %				
Structure	96% natural white meltblown nonwoven fibers(<10 microns)				
	4% white spunbond nonwoven coverstock(<15-30 microns)				
Technology	Meltblown + spunbond				
Absorbency	Universal ( <b>Hydrophilic</b> + Oleophilic)				
Bonding	Bonded (staggered pattern) + Mechanical entanglement				
T. (					

Intended Application	Low -Lint Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids					

Absorbency Capacity147 1 per bale (saturated; medium viscosity-12.5x)

## **Packaging Description:**

Package configuration	Bale	_	Pkg. Weight	11.8 kg (10.1kg)
Items per Package	1 Bale / Case	1	Pkg. Dimensions	45.5 x 45.5 x 78.5 cm
Container type	Carton			70.5 011

## **Physical Properties;**

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	290	29
Caliper	SPCTM-020	mm	4.5	0.4
Absorbency ** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	11.5	1.1
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	
Prody Europe   Industrianark C2   industriant 20   P0240 Zala   Polaium		

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium |

Tel: +32 52.45.7811 | Fax: +32 52.45.7812

www.bradyeurope.com