

## **GENERAL PRODUCT SPECIFICATION**

		7					
Item No.	MS124	]					
Date	16-6-2017	Replaces	10-03-08	No. Pages	1		
Product Description:							
Style		SOC					
Item Size (each)		7,6 cm x 3.6 m					
Color		Gray with red logo printing					
Composition		> 99% Cellulose, < 1% Spundbond					
Structure		Sorbent fill: Micro-fibrous Cellulose					
		Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)					
Technology		Cellulose + Spunbond + Sealed or Enclosed Ends					
Absorbency		Hydrophilic + Oleophilic					
			•				
Intended Application		"Universal" Sorbent Sock for Non-Aggressive Spills of Water Base, Oil Base,					
1	-	or Solvent Base Liquids					
		•	•				
Absorbency Capacity		45 l per bale (saturated; medium viscosity- 8.5x)					
				,			
Packaging <b>D</b>	Description:						
Package conf	figuration	Case	Pkg. V	Weight	5.4kg (4.6kg)		
Items per Pac	ckage	4 Socs/Case	Pkg. 1	Dimensions (approx.)	33 cm x 56 cm x		
	-			\ <b>11</b> /	33 cm (H)		
Container typ	be	Carton					
		•			•		

## Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	Nominal Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	kg	0.73	0.14
Absorbency** (med. oil)	SPCTM-012B	gL/gS	8.5	8-min.
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
_	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	