

TECHNICAL DATA SHEET

Order reference	ODN08
Article number	813801

Date	4-11-11	Replaces	6-29-06	No. Pages	1
Dutt		Iteplaces	0 _/ 00	1100 1 4500	-

Product Description:	
Style	Oil Drag Net
Item Size (each)	15 m section of bundles
Color	Multiple
Composition	Polypropylene filaments or ribbons
Structure	30 bundles of Oil Nets(ONO30) secured along a 15m poly rope
Technology	Meltblown
Absorbency	Hydrophobic + Oleophilic
Intended Application	Sorbent mop nets for heavy viscous oil clean up from off of pilings, seawalls,
	rocks, and the like. Can be reused by rinsing in #1 or #2 fuel oil or similar.
Absorbency Capacity	57 l per Bale (saturated; medium viscosity- 6.6x)

Packaging Description:

Package configuration	Bale	Pkg. Weight	7.4kg
Items per Package	1 Rope/Bale	Pkg. Dimensions (approx.)	33cm dia x 74cm
			Н
Container type	Polybag + Twist Tie		

Physical Properties:

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Absorb. Cap.** (Med	SPCTM-004	liter/net	57	45-min
visc.)				
Color	Visual		Multiple	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com