

Order refe	erence	OIL56	1			
Article nu	mber	813779	1			
		•				
Date	6-29-	06	Replaces	New	No. Pages	1

Style	SOC			
Item Size (each)	7.6 cm d x 17 m long (incl 30 plastic straps)			
Color	White with blue logo printing			
Composition	100% Polypropylene			
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)			
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)			
Technology	Meltblown + Spunbond + Sealed or Enclosed Ends			
Absorbency	Hydrophobic + Oleophilic			
Intended Application	Chemical Resistant Sorbent Sock for Spills of Oil Base or Solvent Base			
	Liquids			

Absorbency Capacity49 1 per case (saturated; medium viscosity- 9x)

Packaging Description:

Package configuration	Case	Pkg. Weight	5.7 kg (4.7 kg)
Items per Package	1 SOC/Case + 30	Pkg. Dimensions (approx.)	56.5 cm x 32cm x
	^plastic straps		37.5cm
Container type	Carton		

Physical Properties;

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	kg	4.7	0.5
Absorbency** (med. oil)	SPCTM-012B	gL/gS	9	8-min.
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	tification Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	
Brady Europe Industriepark C3 Lindestraat 20 B9240 Zele Belgium		

Tel: +32 52.45.7811 | Fax: +32 52.45.7812

www.bradyeurope.com