

Order reference	OIL806
Article number	813777

Date 6-29	9-06 Replaces	3-20-01	No. Pages	1
------------------	---------------	---------	-----------	---

Product Description:

Troduct Description:	
Style	SOC
Item Size (each)	7.6 cm d x 244 cm long
Color	White with blue logo printing
Composition	100% Polypropylene
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)
Technology	Meltblown + Spunbond + Sealed or Enclosed Ends
Absorbency	Hydrophobic + Oleophilic

Intended Application	Chemical Resistant Sorbent Sock for Spills of Oil Base or Solvent Base			
	Liquids			

Absorbency Capac	43 1 per case (saturated; medium viscosity- 9x)	
-------------------------	---	--

Packaging Description:

Package configuration	Case	Pkg. Weight	5 kg (4.1 kg)
Items per Package	6 SOCS/Case	Pkg. Dimensions (approx.)	56.5 cm x32cm x 37.5 cm
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	kg	0.68	0.13
Absorbency** (med. oil)	SPCTM-012B	gL/gS	9	8-min.
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of

ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.