

## **GENERAL PRODUCT SPECIFICATION**

Item No.	OP200-E
	~

Date	16-6-2017	Replaces	24-09-14	No. Pages	1
				- 100 - 10800	

**Product Description:** 

orated on centerline for dividing in half for smaller applications  1 cm
1 cm
ypropylene
al white meltblown nonwoven fibers(<10 microns)
spunbond nonwoven coverstock(<15-30 microns)
n + spunbond
obic + Oleophilic
taggered pattern) + Mechanical entanglement

Intended Application	Low -Lint Chemical Resistant Sorbent for Oil and Solvent Base Liquids

Absorbency Canacity	159 l per bale (saturated; medium viscosity-16x)
Absorbency Capacity	137 I per bare (saturated, inedium viscosity-10x)

Packaging Description:

I deliaging b eserristion.	_		
Package configuration	1-Case	Pkg. Weight	9.5 kg (8.6 kg)
Items per Package	200 pads/Case	Pkg. Dimensions	53 cm x 43 cm x 54 cm (H)
Container type	Carton		

## Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Basis Weight	SPCTM-002A	g/m2	205	20
Caliper	SPCTM-020	mm	3.3	0.3
Absorbency ** (med.	SPCTM-004B	gL/gS	16	1.6
Oil)				
Tensile Strength	SPCTM-007	daN	20	2
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Labeling</b> Each package to be clearly labeled with Company Name, Address, Item	
_	Date, and/or Package Code (Bar Code).
<b>Certification</b> Make no changes in basic process or composition without notifying	
	Claims for non-conformance of goods must be made within 60-days of delivery.