

Order refere	nce RF30	
umł		
mł	er 81393	
	I	
Date	17-10-08	Replace

Product Description:	
Style	Pads
Item Size (each)	38 cm x 48 cm
Color	Off-white
Composition	100% celluslose
Structure	1-ply – Non-woven mat of randomly oriented cellulose fibers
Absorbency	Hydrophilic + Oleophilic
Bonding	Mechanical entanglement
-	·
Intended Application	Sorbent for Water, Oil, or Solvent Base Liquids

Absorbency Capacity	121 l per bale (saturated; medium viscosity-12.5x)
Those beney Capacity	121 1 per bare (saturated, incuratin viscosity 12.5X)

Packaging Description:

Package configuration	1-Case	Pkg. Weight	6.7 kg (5.7 kg)
Items per Package	100-Pads/Case	Pkg. Dimensions	51 cm x 41 cm x 51cm H
Container type	Carton		

Physical Properties:

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	310	31
Caliper	SPCTM-020	mm	5.4	0.5
Absorbency** (med.	SPCTM-004B	gL/gS	18.5	1.8
Oil)				
Tensile Strength	SPCTM-007	daN	5	0.5
Color	Visual		Off-white	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
_	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com