

Order reference	RFDP300
Article number	813944

	Date	4-11-11	Rep	laces	5/1/09		No. Pages	1
--	------	---------	-----	-------	--------	--	-----------	---

Product Description:

Style	Pads with Coverstock on both sides. Perforated on centerline for dividing in			
	half for smaller applications.			
Item Size (each)	15" x 19"			
Color	Off-White			
Composition	95% cellulose 5% PP/PE spunbond (SB used to add strength and durability)			
Structure	3 Ply - Nonwoven mat of randomly oriented cellulose fibers			
Absorbency	Hydrophilic + Oleophilic			
Bonding	Mechanical entanglement			

Intended Application	Sorbent for Water, Oil, or Solvent Base Liquids
----------------------	---

(saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	1-case		Pkg. Weight	7.5kg (6.5kg)
Items per Package	100-Pads/case	_	Pkg. Dimensions	51cm x 41cm x
				51cm H
Container type	Carton			

Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	355	39
Caliper	SPCTM-003A	mils	211	25
Absorbency**	SPCTM-004B	gL/gS	16.5	1.6
(med.visc.)				
Tensile Strength	SPCTM-007	lbs	30	3
Color	Visual		Off-White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.