

Product Description:

Blanket Roll; perforated every 19" for single or multiple/variable length pads.		
a) 14.25" wide by 150' long		
Off-White		
95% cellulose 5% PP/PE spunbond (SB used to add strength and durability)		
3 Ply - Nonwoven mat of randomly oriented cellulose fibers		
Hydrophilic + Oleophilic		
Mechanical entanglement		
Sorbent for Water, Oil, or Solvent Base Liquids		

Absorbency Capacity 104 l per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	1-case	Pkg. Weight	7.5kg (6.5kg)
Items per Package	1 roll/case	Pkg. Dimensions	61cm x 61cm x 31cm H
Container type	Carton		

Physical Properties:

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	355	35
Caliper	SPCTM-003A	mils	200	2
Absorbency**	SPCTM-004B	gL/gS	15.5	1.5
(med.visc.)				
Tensile Strength	SPCTM-007	lbs	30	3
Color	Visual		Off-White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.		
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,		
_	Date, and/or Package Code (Bar Code).		
Certification	tion Make no changes in basic process or composition without notifying customer.		
	Claims for non-conformance of goods must be made within 60-days of delivery.		

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com