

Order reference	SPC100-E		
Article number	813736		

Date	4-11-11	Replaces	6-12-06	No. Pages	1

Product Description:

Style	Pads; perforated on centerline for dividing in half for smaller applications				
Item Size (each)	41 cm x 51 cm perf at 25.5cm				
Color	White				
Composition	100% Polypropylene				
Structure	Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]				
Technology	Meltblown, 1-ply				
Absorbency	Hydrophobic + Oleophilic				
Bonding	Mechanical entanglement, dimpled (no Spunbound)				

Intended Application	Chemical Resistant Sorbent for Oil & Solvent Base Liquids
intellaca ripplication	Chemical Resistant Soldent for On & Solvent Base Enquies

|--|

Packaging Description:

Package configuration	1 Case		Pkg. Weight	8.3 kg (7.3 kg)
Items per Package	100 pads/Case	_	Pkg. Dimensions	43cm x 52cm x 44cm H
Container type	Carton			

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	350	35
Caliper	SPCTM-020	mm	6.5	0.6
Absorbency**	SPCTM-004B	gL/gS	13.5	2
(med.visc.)				
Tensile Strength	SPCTM-007	daN	8.6	0.8
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of

ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.				
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,				
	Date, and/or Package Code (Bar Code).				
Certification	Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.				