

## Order reference SPC152

Date	4-11-11	Replaces	6-13-06	No. Pages	1

<b>Product Description:</b>		
Style	Blanket rolls	
Item Size (each)	48 cm x 44 m	
Color	White	
Composition	100% Polypropylene	
Structure	Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]	
Technology	Meltblown, 1-ply	
Absorbency	Hydrophobic + Oleophilic	
Bonding	Mechanical entanglement, dimpled (no Spunbound)	
Intended Application "Half-Size" Chemical Resistant Sorbent BLANKETS for Oil & So		
	Liquids.	

**Absorbency Capacity** 2311 per bale (saturated; medium viscosity-13.5x)

## **Packaging Description:**

Article number

813760

Package configuration	Bale		Pkg. Weight	15.0 kg (14.8 kg)
Items per Package	2-Blankets/Bale	-	Pkg. Dimensions	47cm dia x 97cm H.
Container type	Polybag + Twist-Tie			

## **Physical Properties;**

Parameter	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	350	35
Caliper	SPCTM-020	mm	6.5	0.6
Absorbency** (med.visc.)	SPCTM-004B	gL/gS	13.5	2
Tensile Strength	SPCTM-007	daN	8.6	0.8
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com