

# **TECHNICAL DATA SHEET**

Date 4-11-11 Replaces 6-19-06 No. Pages 1
---

## **Product Description:**

I Touuct Description.			
Style	Perforated Blanket; perforated every 44cm (100 pads)		
Item Size (each)	48cm x 44 m (100 pads per roll)		
Color	Natural white one side, blue on the other		
Composition	100% Polypropylene		
Structure	96% natural white meltblown nonwoven fibers(<10 microns)		
	4% blue spunbond nonwoven coverstock(<15-30 microns)		
Technology	Meltblown and spunbond fibers		
Absorbency	Hydrophobic + Oleophilic		
Bonding	Bonded (staggered pattern) + Mechanical entanglement		
Intended Application	High strength, shed resistant, chemical resistant oil sorbent roll		

Absorbency Capacity 244 1 per bale (saturated; medium viscosity-13.5x)

## **Packaging Description:**

Package configuration	Bale	Pkg. Weight	15.8 kg (15.6 kg)
Items per Package	2 Rolls/Bale (200	Pkg. Dimensions	Dia. 43 cm x 97cm H
	pads)		
Container type	Polybag + Twist-Tie		

#### **Physical Properties;**

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	365	36
Caliper	SPCTM-020	mm	6.5	0.6
Absorbency**	SPCTM-004B	gL/gS	13.5	2
(med.visc.)				
Tensile Strength	SPCTM-007	daN	13.8	1.3
Color	Visual		White/blue back	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of

## ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

/ 8	$\frac{1}{2}$	
Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,	
_	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com