

Order reference		SPC1	.55				
Article number		8137	57				
Date	6-19-06		Replaces	New	No. Page	s 1	

Product Description:

Style	Perforated Blanket; perforated every 44cm (100 pads)		
Item Size (each) 96cm x 44 m (100 pads per roll)			
Color	Natural white one side, blue on the other		
Composition	100% Polypropylene		
Structure	96% natural white meltblown nonwoven fibers(<10 microns)		
	4% blue spunbond nonwoven coverstock(<15-30 microns)		
Technology Meltblown and spunbond fibers			
Absorbency Hydrophobic + Oleophilic			
Bonding Bonded (staggered pattern) + Mechanical entanglement			

Intended Application	High strength, shed resistant, chemical resistant oil sorbent roll
-----------------------------	--

Absorbancy Canacity	244 1 per Roll (saturated; medium viscosity-13.5x)
Absolutincy Capacity	277 1 per Ron (saturated, medium viscosity-13.3x)

Packaging Description:

Package configuration	Bale	Pkg. Weight	15.8 kg (15.6 kg)
Items per Package	1 Roll/Bale (100	Pkg. Dimensions	Dia. 43 cm x 97cm H
	pads)		
Container type	Polybag + Twist-Tie		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	365	36
Caliper	SPCTM-020	mm	6.5	0.6
Absorbency**	SPCTM-004B	gL/gS	13.5	2
(med.visc.)				
Tensile Strength	SPCTM-007	daN	13.8	1.3
Color	Visual		White/blue back	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of

ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

115 11/11 : 20, using 511220 non-decorgon dis the On-1/pe, mediam (1500510)					
Attributes Product will be free of foreign material contamination, rips, holes, and					
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,				
	Date, and/or Package Code (Bar Code).				
Certification	Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.				