

Order reference	SPC200-3-E
Article number	813739

Date	4-11-11	Replaces	12-11-06	No. Pages	1
2		220 122000	12 11 00	1100 1 45	-

## **Product Description:**

Style	Pads	
Item Size (each)	30 cm x 30 cm	
Color	White	
Composition	100% Polypropylene	
Structure	Nonwoven mat of randomly oriented Micro-fibers [4-10 micron diameters]	
Technology	Meltblown, 1-ply	
Absorbency	Hydrophobic + Oleophilic	
Bonding	Mechanical entanglement, dimpled (no Spunbound)	

Intended Application Chemical Resistant Sorbent for Oil & Solvent Base Liquids
--

Abaarbanar Canaaitu	71 I man hala (activisted) madisum viscosity 10v)
Ausurbency Capacity	71 l per bale (saturated; medium viscosity-18x)

## **Packaging Description:**

Package configuration	1-Bale	Pkg. Weight	3.5 kg (3.4 kg)
Items per Package	200-Pads/Bale	Pkg. Dimensions	33cm x 33cm x
			51cm H
Container type	Polybag + Twist-Tie		

## **Physical Properties**;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	190	19
Caliper	SPCTM-020	mm	4.0	0.4
Absorbency**	SPCTM-004B	gL/gS	18	2
(med.visc.)				
Tensile Strength	SPCTM-007	daN	6.0	0.6
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.