

Article number 813767

Date 1-3-11 Replaces 6-29-06 No. Pages 1	Date		Replaces	6-29-06	No. Pages	1	
---------------------------------------------------------------	------	--	----------	---------	-----------	---	--

Product Description:	
Style	Standard Lint-Free Boom
Item Size (each)	20 cm dia x 3 m long
Color	White
Composition	>95% Polypropylene; <5% Nylon (netting); metal clips
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)
	Inner covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)
	Outer covering: Knitted Polyester yarn netting.
	Inter-connection Fasteners: Rope; Rings; Breach Clips; Tipper-Tie closures.
Technology	Meltblown + Spunbond + Tipper-Tie end closures + Modular Connection
Absorbency	Hydrophobic + Oleophilic
Intended Application	Inter Connecting Chemical Resistant "Lint Free" Sorbent Booms for Spills of
	Oil Base or Solvent Base Liquids

Absorbency Capacity 3161 bale (saturated; medium viscosity-13 x)

Packaging Description:

Package configuration	Bale	Pkg. Weight	21.2 kg (21.0 kg)
Items per Package	4 Booms/Bale	Pkg. Dimensions (approx.)	79cm dia x 70cm
			Н
Container type	Polybag & Twist-tie		

Physical Properties;

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Boom Weight	Gravimetric	kg	5.25	0.45
Absorbency** (med. oil)	SPCTM-012B	gL/gS	13.0	12-min.
Color	Visual		White	per standard
Netting Tensile Strength		daN	1134	per specification

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.

Brady Europe | Industriepark C3 Lindestraat 20 | B9240 Zele | Belgium | Tel: +32 52.45.7811 | Fax: +32 52.45.7812 www.bradyeurope.com