

Order reference	SPC816-E
Article number	813768

Date 4-11-11 Repla	ces 6-29-06	No. Pages	1
----------------------------------	-------------	-----------	---

Product Description:

Style	Standard lint-free Boom
Item Size (each)	20 cm dia x 5 m long
Color	White
Composition	>95% Polypropylene; <5% Nylon (netting); metal clips
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters) Inner covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber) Outer covering: Knitted Polyester yarn netting. Inter-connection Fasteners: Black Rope; Rings; Clips; Tipper-Tie closures
Technology	Meltblown + Spunbond + Tipper-Tie end closures + Modular Connection
Absorbency	Hydrophobic + Oleophilic

Intended Application	Lint-free chem resistant sorbent boom for non-aqueous spills on land & water

Absorbency Capacity	263 l per bale (saturated)
----------------------------	----------------------------

Packaging Description:

Package configuration	Bale	Pkg. Weight	17.7 kg (17.5 kg)
Items per Package	2 Booms/Bale	Pkg. Dimensions	76cm dia x 64cm high
Container type	Polybag + Twist-Tie		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Boom Weight	W.I.P.	kg	9.1	0.9
Absorbency**	SPCTM-012B	gL/gS	13	11-min
(med.visc.)				
Tensile	ASTM D-1682	daN	102	10
Color	Visual		White	per standard
Netting Tensile Strength		kg	1134	per specification

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of

ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.