

## TECHNICAL DATA SHEET

Order reference SXT315-		15-	Р-Е				
Article number		81374	8	•			
Date	4-11	-11		Replaces	03-31-08	No. Pages	1

## **Product Description:**

Style	Blanket Roll; high strength perforation every 46cm for single or multiple/variable length pads			
Item Size (each)	38 cm x 46 m (100 pads)			
Color	White			
Composition	100% Polypropylene			
Structure	A bonded trilaminate nonwoven mat wherein the middle white layer is randomly oriented meltblown micro-fibers [2-10 micron diameters], and the coverstock layers are lint-resistant & abrasion resistant {controlled porosity} spunbond nonwoven of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters].			
Technology	Spunbond & Meltblown (3-ply construction)			
Absorbency	Hydrophobic + Oleophilic			
Bonding	Bonded (staggered pattern) + Mechanical entanglement			

Intended Application	Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or
	Solvent Base Liquids

<b>Absorbency Capacity</b>	70 1 per Roll (saturated; medium viscosity-13.5x)
----------------------------	---

## **Packaging Description:**

Package configuration	Case	Pkg. Weight	6.3 kg (5.1 kg)
Items per Package	1 Roll / Case	Pkg. Dimensions	43cm x 43cm x
	100 pads		38cm H
Container type	Carton		

## **Physical Properties**;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	290	29
Caliper	SPCTM-003	mm	4.6	0.4
Absorbency** (med.	SPCTM-004B	gL/gS	12	2
Oil)				
Tensile Strength	SPCTM-007	daN	30	3
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

using 57x220 non-actergent as the On Type, medium viscosity.					
Attributes	Product will be free of foreign material contamination, rips, holes, and tears.				
<b>Labeling</b> Each package to be clearly labeled with Company Name, Address, Item N					
	Date, and/or Package Code (Bar Code).				
Certification	Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.				