

TECHNICAL DATA SHEET

Order reference SX		SXT	Г330-DР-Е			
Article number		813′	749			
Date	4-11-11		Replaces	03-31-08	No. Pages	1

Product Description:

Style	Blanket Roll; high strength perforation every 46cm for single or multiple/variable length pads		
Item Size (each)	76 cm x 46 m (200 pads)		
Color	White		
Composition	100% Polypropylene		
Structure	A bonded trilaminate nonwoven mat wherein the middle white layer is randomly oriented meltblown micro-fibers [2-10 micron diameters], and the coverstock layers are lint-resistant & abrasion resistant {controlled porosity} spunbond nonwoven of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters].		
Technology	Spunbond & Meltblown (3-ply construction)		
Absorbency	Hydrophobic + Oleophilic		
Bonding	Bonded (staggered pattern) + Mechanical entanglement		

Intended Application	Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or
	Solvent Base Liquids

Absorbency Capacity 141 1 per Roll (saturated; medium viscosity-13.5x)

Packaging Description:

Package configuration	Case	Pkg. Weight	11.8 kg (10.2 kg)
Items per Package	1 Roll / Case	Pkg. Dimensions	43cm x 43cm x
	200 pads		77cm H
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	<u>Nominal</u>	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	290	29
Caliper	SPCTM-003	mm	4.6	0.5
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	12	2
Tensile Strength	SPCTM-007	daN	14	1.4
Color	Visual		White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

using brilled non de	tergent as the On Type, meatain viscosity.				
Attributes	Product will be free of foreign material contamination, rips, holes, and tears.				
Labeling Each package to be clearly labeled with Company Name, Address, Iter					
	Date, and/or Package Code (Bar Code).				
Certification	Make no changes in basic process or composition without notifying customer.				
	Claims for non-conformance of goods must be made within 60-days of delivery.				