

Order reference		UN1	1212	-Е			
Article number		8138	843				
-Date	4-11-1	1]	Replaces	03-31-08	No. Pages	1

Product Description:

Style	Pads with dispenser box	
Item Size (each)	30 cm x 30 cm	
Color	Green	
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %	
Structure	96% natural white meltblown nonwoven fibers(<10 microns)	
	4% white spunbond nonwoven coverstock(<15-30 microns)	
Technology	Meltblown + spunbond	
Absorbency	Universal (Hydrophilic + Oleophilic)	
Bonding	Bonded (staggered pattern) + Mechanical entanglement	

Intended Application	Low -Lint Chemical & Static Resistant Sorbent for Water, Oil, or Solvent Base
	Liquids

Absorbency Capacity	76 l per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	4-Bags/Case	Pkg. Weight	6.7 kg (5.2 kg)
Items per Package	4 x 50-Pads	Pkg. Dimensions	67cm x 40cm x
			35.5cm H
Container type	Polybags + Carton		

Physical Properties;

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	290	29
Caliper	SPCTM-020	mm	4.5	0.4
Absorbency** (med	SPCTM-004B	gL/gS	12.5	2
visc)				
Tensile Strength	SPCTM-007	daN	12	1.2
Color	Visual		Green	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.
** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.			
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,			
	Date, and/or Package Code (Bar Code).			
Certification	Make no changes in basic process or composition without notifying customer.			
	Claims for non-conformance of goods must be made within 60-days of delivery.			